

HYTEX® RIB

Vertical Surfaces | Partitions | Acoustical Panels



GHOST
19-210



PORCELAIN
19-212



PARCHMENT
24-03



BEACH
19-87



CINNABAR
19-207



ALMOND
19-211



ABALONE
19-219



LACE
19-209



CURRY
19-216



SCARLET
19-200




MARBLE
19-61



LINEN
19-206



TAFFY
19-17



HUNTER
19-215



RUBY
24-23




FLAGSTONE
19-22



TAUPE
19-62




MOCHA
19-202



TEAL
19-203



MARINE
19-208




GUNMETAL GREY
24-06




SEPIA
19-213




SUMATRA
19-85




DANUBE
19-217




NAVY
19-27



BLACK
19-33



CHARCOAL
19-57



JUNIPER
19-220



CERULEAN
19-218



VERDIGRIS
19-214

HYTEX[®]RIB

Wallcoverings • Panels • Exhibits • Partitions

Vertical channels texturize walls with professional-grade sound absorption made from post-consumer recycled fibers and styled in a modern designer palette.

USAGE AREAS

DESIGNERS

- Commercial Interiors Market

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center

Acoustical Panels • Tack Boards • Elevators • Ceiling Tiles • Office Partitions • Chair Rails

SPECIFICATIONS

WIDTH:	54"	NRC:	(ASTM C-423) 0.20
WEIGHT:	24 ounces / Face Weight	FLAMMABILITY:	Passes NFPA 265 Meets Class A for ASTM E-84
CONTENT:	Recycled Polyester	COLORFASTNESS TO LIGHT:	(AATCC-16) Class 5
BACKING:	Fused Poly	ABRASION RESISTANCE:	Full Commercial Serviceability
ROLL SIZE:	33 yards		

Easy to Clean and Maintain • Velcro Compatible

ENVIRONMENTAL

100% recycled content from water and soda bottles.

Created with no PVC (polyvinyl chloride), VOC's (volatile organic compounds), ODS's (ozone depleting substances), Heavy Metals or Formaldehyde.

Can contribute towards LEED points.

INSTALLATION

Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.

For best results, it is recommended that a qualified textile wallcovering installer be employed.

HYTEX[®]
YORK CONTRACT

WWW.HYTEX.COM

